



LED lamp

ELD-935-525


Radiation	Type	Technology	Case
Infrared	Water clear	AlGaAs/GaAs	5 mm plastic lens

Description

High-power, high-speed, heterostructure, with standoff leads

Applications

Optical communications, safety equipment, automation



Note: Special packages with standoff available on request

Maximum Ratings

$T_{amb} = 25^\circ\text{C}$, unless otherwise specified

Parameter	Test conditions	Symbol	Value	Unit
Forward current (DC)		I_F	100	mA
Peak forward current	($t_P \leq 50 \mu\text{s}$, $t_P/T = 1/2$)	I_{FM}	200	mA
Surge forward current	($t_P \leq 10 \mu\text{s}$)	I_{FSM}	2000	mA
Reverse voltage	$I_R = 100 \mu\text{A}$	V_R	5	V
Operating temperature range		T_{amb}	-20 to +100	°C
Storage temperature range		T_{stg}	-55 to +100	°C
Soldering temperature	$t \leq 5 \text{ s}$, 3 mm from case	T_{sd}	260	°C

Optical and Electrical Characteristics

$T_{amb} = 25^\circ\text{C}$, unless otherwise specified

Parameter	Test conditions	Symbol	Min	Typ	Max	Unit
Forward voltage	$I_F = 100 \text{ mA}$	V_F		1.4	1.6	V
Radiant power	$I_F = 100 \text{ mA}$	Φ_e	20	30		mW
Radiant intensity	$I_F = 100 \text{ mA}$	I_e	70	100		mW/sr
Peak wavelength	$I_F = 20 \text{ mA}$	λ_p	925	935	950	nm
Spectral bandwidth at 50%	$I_F = 20 \text{ mA}$	$\Delta\lambda_{0.5}$		65		nm
Viewing angle	$I_F = 20 \text{ mA}$	ϕ		20		deg.
Switching time	$I_F = 100 \text{ mA}$	t_r, t_f		500		ns