



## LED545-66-60

- Green High Power LED Array
- 545 nm, 140 mW
- Chip: 350x350  $\mu\text{m}$ , 60 pcs., InGaN
- TO-66 package, Silicone and/or Epoxy resin
- Viewing Angle: 118°



### Description

**LED545-66-60** is a wide viewing and extremely high output power illuminator consists of 60 pcs. of InGaN chip dies, mounted on a metal stem TO-66 package with AlN ceramics and covered with clear silicone and/or epoxy resin.

On forward bias, it emits a power radiation of typical **140 mW** at a peak wavelength of **545 nm**.

### Maximum Ratings ( $T_{CASE}=25^{\circ}\text{C}$ )

Parameter	Symbol	Values		Unit
		Min.	Max.	
Power Dissipation	$P_D$		12	W
Forward Current	$I_F$		600	mA
Reverse Voltage	$V_R$		25	V
Thermal Resistance	$R_{THJA}$		2	K/W
Junction Temperature	$T_J$		120	$^{\circ}\text{C}$
Operating Temperature	$T_{CASE}$	- 40	+ 85	$^{\circ}\text{C}$
Storage Temperature	$T_{STG}$	- 40	+ 100	$^{\circ}\text{C}$
Lead Solder Temperature *	$T_{SLD}$		+ 265	$^{\circ}\text{C}$

\* must be completed within 3 seconds






### Electro-Optical Characteristics ( $T_{CASE}=25^{\circ}\text{C}$ )





Parameter	Symbol	Conditions	Values			Unit
			Min.	Typ.	Max.	
Peak Wavelength	$\lambda_P$	$I_F=240\text{mA}$	535		555	nm
Dominant Wavelength	$\lambda_D$	$I_F=240\text{mA}$		555		nm
Half Width	$\Delta\lambda$	$I_F=240\text{mA}$		40		nm
Forward Voltage	$V_F$	$I_F=240\text{mA}$		17	19	V
Radiated Power *	$P_O$	$I_F=240\text{mA}$		140		mW
Luminous Flux	$\Phi_V$	$I_F=240\text{mA}$		120		mlm
Viewing Angle	$2\theta_{1/2}$	$I_F=100\text{mA}$		118		deg.
Rise Time	$t_R$	$I_F=240\text{mA}$		15		ns
Fall Time	$t_F$	$I_F=240\text{mA}$		30		ns

\* measured by S3584-08



## Typical Performance Curves





## Outline Dimensions

LED545-66-60
TO-66

Lead	Description
Pin 1	LED Anode
Pin 2	LED Cathode

All Dimensions in mm



## Precautions

---

### Cautions:

- This high power LED must be cooled!
- NOT look directly into the emitting area of the LED during operation!

### Soldering:

- Do avoid overheating of the LED
- Do avoid electrostatic discharge (ESD)
- Do avoid mechanical stress, shock, and vibration
- Do only use non-corrosive flux
- Do not apply current to the LED until it has cooled down to room temperature after soldering

### Cleaning:

**Cleaning with isopropyl alcohol, propanol, or ethyl alcohol is recommended**

DO NOT USE acetone, chloroform, trichloroethylene, or MKS

DO NOT USE ultrasonic cleaners

### Static Electricity:

**LEDs are sensitive to electrostatic discharge (ESD).** Precautions against ESD must be taken when handling or operating these LEDs. Surge voltage or electrostatic discharge can result in complete failure of the device.

### Radiation:

During operation these LEDs do emit **high intensity light**, which is hazardous to skin and eyes, and may cause cancer. Do avoid exposure to the emitted light. **Protective glasses are recommended.** It is further advised to attach a warning label on products/systems.

### Operation:

**Do only operate LEDs with a current source.**

Running these LEDs from a voltage source will result in complete failure of the device.

Current of a LED is an exponential function of the voltage across it. Usage of current regulated drive circuits is mandatory.



## Revisions History

---

Rev.	Rel. Date	Chapter	Modification	Page
A1	2018-12-01	-	Initial release	-

---

© All Rights Reserved

The above specifications are for reference purpose only and subjected to change without prior notice