

**PRELIMINARY**

Rev. A1

## SMB1N-700D-02

- High Power LED
- 700 nm, 200 mW
- SMD package, PA9T
- Dimension: 5.0 x 5.2 x 5.5 mm
- Viewing Angle: 20°



### Description



**SMB1N-700D-02** is a surface mount AlGaInP High Power LED with a typical peak wavelength of **700 nm** and radiation of **200 mW**. It comes in SMD package (PA9T) with silver plated soldering pads (lead free solderable), copper heat sink, and molded with silicone resin.

### Maximum Ratings ( $T_{CASE}=25^{\circ}C$ )

| Parameter                  | Symbol     | Values |       | Unit |
|----------------------------|------------|--------|-------|------|
|                            |            | Min.   | Max.  |      |
| Power Dissipation          | $P_D$      |        | 1200  | mW   |
| Forward Current            | $I_F$      |        | 500   | mA   |
| Pulse Forward Current *1   | $I_{FP}$   |        | 2000  | mA   |
| Reverse Voltage            | $V_R$      |        | 5     | V    |
| Thermal Resistance         | $R_{THJA}$ |        | 10    | K/W  |
| Junction Temperature       | $T_J$      |        | 120   | °C   |
| Operating Temperature      | $T_{CASE}$ | - 40   | + 100 | °C   |
| Storage Temperature        | $T_{STG}$  | - 40   | + 100 | °C   |
| Lead Solder Temperature *2 | $T_{SLD}$  |        | + 250 | °C   |

\*1 duty=1%, pulse width = 10  $\mu$ s

\*2 must be completed within 5 seconds

### Electro-Optical Characteristics ( $T_{CASE}=25^{\circ}C$ )







| Parameter            | Symbol          | Conditions  | Values |      |      | Unit  |
|----------------------|-----------------|-------------|--------|------|------|-------|
|                      |                 |             | Min.   | Typ. | Max. |       |
| Peak Wavelength      | $\lambda_P$     | $I_F=500mA$ | 690    |      | 710  | nm    |
| Half Width           | $\Delta\lambda$ | $I_F=500mA$ |        | 19   |      | nm    |
| Forward Voltage      | $V_F$           | $I_F=500mA$ |        | 2.1  | 2.3  | V     |
|                      | $V_{FP}$        | $I_{FP}=2A$ |        | 2.6  |      |       |
| Radiated Power *1    | $P_O$           | $I_F=500mA$ |        | 200  |      | mW    |
|                      |                 | $I_{FP}=2A$ |        | 770  |      |       |
| Radiant Intensity *2 | $I_E$           | $I_F=500mA$ |        | 540  |      | mW/sr |
|                      |                 | $I_{FP}=2A$ |        | 2000 |      |       |
| Viewing Angle        | $\varphi$       | $I_F=100mA$ |        | 20   |      | deg.  |
| Rise Time            | $t_R$           | $I_F=500mA$ |        | 40   |      | ns    |
| Fall Time            | $t_F$           | $I_F=500mA$ |        | 50   |      | ns    |





\*1 measured by S3584-08

\*2 measured by CIE127-2007 Condition B




## Typical Performance Curves





## Outline Dimensions



All Dimensions in mm



## Precautions



### Soldering:

- Do avoid overheating of the LED
- Do avoid electrostatic discharge (ESD)
- Do avoid mechanical stress, shock, and vibration
- Do only use non-corrosive flux
- Do not apply current to the LED until it has cooled down to room temperature after soldering

### Recommended soldering conditions:

This LED is designed to be reflow soldered on to a PCB. If dip soldered or hand soldered, its reliability cannot be guaranteed.

Nitrogen reflow soldering is recommended. Air flow soldering conditions can cause optical degradation, caused by heat and/or atmosphere.



Above table specifies the maximum allowed duration and temperature during soldering. It is strongly advised to perform soldering at the shortest time and lowest temperature possible.

### Cleaning:

**Cleaning with isopropyl alcohol, propanol, or ethyl alcohol is recommended**

DO NOT USE acetone, chloroform, trichloroethylene, or MKS

DO NOT USE ultrasonic cleaners

### Static Electricity:

LEDs are sensitive to electrostatic discharge (ESD). Precautions against ESD must be taken when handling or operating these LEDs. Surge voltage or electrostatic discharge can result in complete failure of the device.

### Radiation:

During operation these LEDs do emit **high intensity light**, which is hazardous to skin and eyes, and may cause cancer. Do avoid exposure to the emitted light. **Protective glasses are recommended.** It is further advised to attach a warning label on products/systems.

### Operation:

**Do only operate LEDs with a current source.**

Running these LEDs from a voltage source will result in complete failure of the device.

Current of a LED is an exponential function of the voltage across it. Usage of current regulated drive circuits is mandatory.



## Revisions History

---

| Rel. | Rel. Date  | Chapter | Modification    | Page |
|------|------------|---------|-----------------|------|
| A1   | 2020-09-30 | -       | Initial release | -    |

---

© All Rights Reserved

The above specifications are for reference purpose only and subjected to change without prior notice