



ROITHNER LASERTECHNIK GmbH

WIEDNER HAUPTSTRASSE 76
TEL. +43 1 586 52 43 -O, FAX. -44

1040 VIENNA AUSTRIA
OFFICE@ROITHNER-LASER.COM



UV340-T46L

- DEEP UV Light Emitting Device
- 335 nm, 4.8 mW
- TO46 Metal Can Package
- Hemispherical Glass Lens
- Beam Angle: $\pm 7^\circ$



Description



UV340-T46L is a deep ultraviolet LED, typically emitting at **335 nm** with an optical output power of **4.8 mW @ 20 mA**, and narrow bandwidth. It comes in a hermetically sealed TO46 metal can package with hemispherical glass lens, and is typically used for medical applications, diagnostics, and laboratory testing.

Maximum Ratings*

Parameter	Symbol	Values		Unit
		Min.	Max.	
Power Dissipation	P_D		180	mW
Forward Current	I_F		30	mA
Pulse Forward Current**	I_{FP}		100	mA
Reverse Voltage	U_R		10	V
Reverse Current	I_R		1	μA
Operating Temperature	T_{OPR}	- 30	+ 85	$^\circ C$
Storage Temperature	T_{STG}	- 40	+ 100	$^\circ C$
Soldering Temperature (t_{max} 3s)	T_{SLD}		260	$^\circ C$

* Operating close to or exceeding these parameters may damage the device

** duty cycle = 1 %, pulse width = 10 μs

Electro-Optical Characteristics ($T_{CASE} = 25^\circ C$)


Parameter	Symbol	Conditions	Values			Unit
			Min.	Typ.	Max.	
Peak Wavelength	λ_P	$I_F = 20$ mA	330	335	345	nm
Half Width	λ_{Δ}	$I_F = 20$ mA		11		nm
Forward Voltage	U_F	$I_F = 20$ mA	3.0	4.0	5.0	V
Total Radiated Power	P_O	$I_F = 20$ mA	2.4	4.8		mW
Beam Angle	$2\theta_{1/2}$	$I_F = 20$ mA		14		deg.
Thermal Resistance	R_{THJA}	$I_F = 20$ mA		5		K/W





Outline Dimensions

TO46 package



Precautions for Use

Static Electricity:

LEDs are sensitive to electrostatic discharge (ESD). Precautions against ESD must be taken when handling or operating these LEDs. Surge voltage or electrostatic discharge can result in complete failure of the device.

UV-Radiation:

During operation these LEDs do emit **high intensity ultraviolet light**, which is hazardous to skin and eyes, and may cause cancer. Do avoid exposure to the emitted UV light. **Protective glasses are recommended.** It is further advised to attach a warning label on products/systems that do utilize UV-LEDs:

Operation:

- **Do only operate these LEDs with a current source.**
Current of a LED is an exponential function of the voltage across it. Usage of current regulated drive circuits is mandatory.
- Compliance to the maximum electrical specifications is paramount.

Storage:

- **Recommended storage temperature: ≤ 30 °C**
- **Recommended storage relative humidity: ≤ 70 %**