



FCPD-300-FC

- InGaAs PIN Photodiode
- Ø 300 µm active area
- 0.85 – 1.7 µm spectral range
- FC receptacle package
- High responsivity



Description

FCPD-300-FC is an **InGaAs** PIN photodiode with an active area of Ø 300 µm in a FC receptacle package. It features a wide sensitivity range from 850 nm to 1700 nm, high responsivity, low terminal capacitance, and low dark current.

Maximum Rating

Parameter	Symbol	Values		Unit
		Min.	Max.	
Reverse Voltage ($I_R=10 \mu A$)	V_R		50	V
Forward Current	I_F		10	mA
Operating Temperature	T_{OPR}	- 40	+ 85	°C
Storage Temperature	T_{STG}	- 40	+ 125	°C
Soldering Temperature (max.10s)	T_{SOL}		+ 260	°C

Electro-Optical Characteristics ($T_{CASE} = 23^\circ C$)

Parameter	Symbol	Condition	min.	typ.	max.	Unit
Spectral Range	λ		0.85		1.7	µm
Aperture Diameter	$\varnothing$			300		µm
Peak Sensitivity	λ_P	$V_R=0 V$		1.55		µm
Dark Current	I_D	$V_R=5 V$		0.5		nA
Capacitance	C_J	$V_R=5 V$			6	pF
Responsivity	S_λ	1.31 µm		0.85		A/W
		1.55 µm		0.90		
Rise/Fall time	t_r / t_f	$V_R=5 V$			1.0	ns
Package		Receptacle package with FC con.				







Electrical Connection

Pin Configuration*


Bottom View

Pin #	Function
Pin 1	PD Anode
Pin 2	PD Cathode
Pin 3	Case



* subject to change

Outline Dimensions



All dimensions in mm

© All Rights Reserved

The above specifications are for reference purpose only and subjected to change without prior notice